

# caroma®

CI/SfB	(74.1)	g3
Date	May 2008	

Supersedes all previous issues

## Sydney Low Profile 270 1.6/0.8 gpf (6/3 l) Water Saving Dual Flush High Efficiency Toilet (HET) Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet

# 2.8.13



HIGH EFFICIENCY TOILET  
**HET**

**c-UPC®**  
IAPMO listed for USA & Canada

**Sydney Low Profile 270**  
**1.6/0.8 gpf (6/3 l)**  
**Water Saving**  
**Dual Flush High**  
**Efficiency Toilet (HET)**

**Two Piece Ultra Low Flush (ULF)**  
**Vitreous China Washdown Toilet**



A modern concept close coupled **1.6/0.8 gpf (6/3 l) Sydney Low Profile 270** dual flush high efficiency toilet (HET) featuring unique two button activation providing substantial water saving compared to standard toilets and adjustable rough in and smooth rounded contours for easy cleaning. The closet bowl has been designed with rough in of **10" (255mm) to 12" (305mm)** provided by plastic offset outlet connector option. The overall length from the finished wall is **29<sup>3</sup>/<sub>4</sub>" (760mm)**. This tank is a low profile design for greater installation versatility which incorporates a high performance outlet valve that has been specially developed with the **Sydney 270** bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.6/0.8 gpf (6/3 l) dual flush system the toilet is suitable for multi purpose applications where **water conservation** is important.

- Closet Bowl:** **Sydney 270** 1.6/0.8 gpf (6/3 l) full flush washdown closet bowl with open flushing rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) and 12" (305mm) rough in.
- Tanks:** **Sydney Low Profile Tank** – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas Code No.750110.
- Weight:** 82 lbs (37 kg).
- Water Control Valve:** **Standard Bottom Entry Tank** – available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seats:** The following Caroma seats are recommended: **Caravelle** Code No.301032, **Royale** easy closing Code No. 326222 and **Royale** Code No.326707.
- Colors:** White only.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Sydney Low Profile 270:		Code No.
Tank	LH inlet	622330
Bowl		609159

**HIGH EFFICIENCY TOILET**  
**HET**

**c-UPC®**  
IAPMO listed for USA & Canada

**Note:** All height dimensions to underside of closet bowl, make allowance for bedding.  
**Screw fixing:** The closet bowl should be bedded with an approved silicon caulking and fixed with corrosion resistant screws and closet guard washers. Use Caroma screw fixing kit. Code No. 601150.